Techno ATM

Automated Teller Machine

High speed and large capacity lobby cash dispenser makes cardholders enjoys services not only at bank branches but also at off-premise locations.

- Dispenser: NMD100 (Glory)
- Security: Anti Skimming / Jitter Tech.
- Wide-Angle rearview mirror can effectively improve the opration safety
- Easy maintenance
- EPP complying with PCI 4.0
- Card Reader complying with EMV2000









Automated

Teller Machine | SPECIFICATIONS

Processor System Memory 2G RAM Standard TCP/IP Optional: dial-up, wireless, X.25, SNA/SDLC Display 15" TFT LCD display, voice guidance 8 FDKs Motorized hybrid card reader EMV certified Support magnetic/smart card Storage Device 250G HDD Operating system Prictional bundle delivery Max. 60 notes per bundle Dispenser Prictional bundle delivery Max. 60 notes per second 2-4 cassettes, up to 3000 notes per cassette Reject & retract bin Cassette lock (optional) UL291 Standard level 1 Dial combination lock mechanism Fraudulent device inhibitor (FDI) EPP shield Privacy filter (optional) Customer awareness mirror Built-in cameras Integrated media entry/exit indicators Barcode reader Fingerprint reader Contact-less card reader Heat booster Electronic journal Receipt printer: 76mm thermal graphic printer Journal printer: 80mm dot matrix or thermal printer Voltage 100V-240V AC, 50/60Hz Indoor: 0 oC to 40 oC (without heat booster) humidity: 20% to 95% Non-condensing Physical Weight 269 kg		
Standard TCP/IP Optional: dial-up, wireless, X.25, SNA/SDLC	Processor	Intel core 2 Duo 3.0 CPU
Optional: dial-up, wireless, X.25, SNA/SDLC Display 15" TFT LCD display, voice guidance 8 FDKs Motorized hybrid card reader EMV certified Support magnetic/smart card Storage Device Operating system Dispenser Dial combination lock mechanism Fraudulent device inhibitor (FDI) EPP shield Privacy filter (optional) Customer awareness mirror Built-in cameras Integrated media entry/exit indicators Barcode reader Fingerprint reader Contact-less card reader Heat booster Electronic journal Receipt printer: 76mm thermal graphic printer Journal printer: 80mm dot matrix or thermal printer Voltage Dispenser Dispenser Dispenser Dispenser Dispenser Privacy filter (optional) Customer awareness mirror Built-in cameras Integrated media entry/exit indicators Barcode reader Fingerprint reader Contact-less card reader Heat booster Electronic journal Receipt printer: 76mm thermal graphic printer Journal printer: 80mm dot matrix or thermal printer Dournal printer: 80mm dot matrix or thermal printer Dournal printer: 80mm dot matrix or thermal printer Dournal printer: 80mm dot of without heat booster) Outdoor: 35 oC to 40 oC (with heat booster) humidity: 20% to 95% Non-condensing Height: 1440 mm Width: 450 mm Depth: 870 mm	System Memory	2G RAM
Motorized hybrid card reader EMV certified Support magnetic/smart card	Communication	
Card Reader EMV certified Support magnetic/smart card Storage Device 250G HDD Operating system Window XP Frictional bundle delivery Max. 60 notes per bundle Dispensing speed: 7 notes per second 2-4 cassettes, up to 3000 notes per cassette Reject & retract bin Cassette lock (optional) UL291 Standard level 1 Dial combination lock mechanism Fraudulent device inhibitor (FDI) EPP shield Privacy filter (optional) Customer awareness mirror Built-in cameras Integrated media entry/exit indicators Barcode reader Fingerprint reader Contact-less card reader Heat booster Electronic journal Receipt printer: 76mm thermal graphic printer Journal printer: 80mm dot matrix or thermal printer Voltage 100V-240V AC, 50/60Hz Indoor: 0 oC to 40 oC (without heat booster) humidity: 20% to 95% Non-condensing Height: 1440 mm Width: 450 mm Depth: 870 mm	Display	
Operating system Frictional bundle delivery Max. 60 notes per bundle Dispensing speed: 7 notes per second 2-4 cassettes, up to 3000 notes per cassette Reject & retract bin Cassette lock (optional) UL291 Standard level 1 Dial combination lock mechanism Fraudulent device inhibitor (FDI) EPP shield Privacy filter (optional) Customer awareness mirror Built-in cameras Integrated media entry/exit indicators Barcode reader Fingerprint reader Contact-less card reader Heat booster Electronic journal Receipt printer: 76mm thermal graphic printer Journal printer: 80mm dot matrix or thermal printer Voltage 100V-240V AC, 50/60Hz Indoor: 0 oC to 40 oC (without heat booster) Outdoor: 35 oC to 40 oC (with heat booster) humidity: 20% to 95% Non-condensing Height: 1440 mm Width: 450 mm Depth: 870 mm	Card Reader	EMV certified
Frictional bundle delivery Max. 60 notes per bundle Dispensing speed: 7 notes per second 2-4 cassettes, up to 3000 notes per cassette Reject & retract bin Cassette lock (optional) UL291 Standard level 1 Dial combination lock mechanism Fraudulent device inhibitor (FDI) EPP shield Privacy filter (optional) Customer awareness mirror Built-in cameras Integrated media entry/exit indicators Barcode reader Fingerprint reader Contact-less card reader Heat booster Electronic journal Receipt printer: 76mm thermal graphic printer Journal printer: 80mm dot matrix or thermal printer Voltage 100V-240V AC, 50/60Hz Indoor: 0 oC to 40 oC (without heat booster) Outdoor: 35 oC to 40 oC (with heat booster) humidity: 20% to 95% Non-condensing Height: 1440 mm Width: 450 mm Depth: 870 mm	Storage Device	250G HDD
Dispenser Dispenser Dispensing speed: 7 notes per second 2-4 cassettes, up to 3000 notes per cassette Reject & retract bin Cassette lock (optional) UL291 Standard level 1 Dial combination lock mechanism Fraudulent device inhibitor (FDI) EPP shield Privacy filter (optional) Customer awareness mirror Built-in cameras Integrated media entry/exit indicators Barcode reader Fingerprint reader Contact-less card reader Heat booster Electronic journal Receipt printer: 76mm thermal graphic printer Journal printer: 80mm dot matrix or thermal printer Voltage 100V-240V AC, 50/60Hz Indoor: 0 oC to 40 oC (without heat booster) Outdoor: 35 oC to 40 oC (with heat booster) humidity: 20% to 95% Non-condensing Height: 1440 mm Width: 450 mm Depth: 870 mm	Operating system	Window XP
Dial combination lock mechanism Fraudulent device inhibitor (FDI) EPP shield Privacy filter (optional) Customer awareness mirror Built-in cameras Integrated media entry/exit indicators Barcode reader Fingerprint reader Contact-less card reader Heat booster Electronic journal Receipt printer: 76mm thermal graphic printer Journal printer: 80mm dot matrix or thermal printer Voltage 100V-240V AC, 50/60Hz Indoor: 0 oC to 40 oC (without heat booster) Cutdoor: 35 oC to 40 oC (with heat booster) humidity: 20% to 95% Non-condensing Height: 1440 mm Width: 450 mm Depth: 870 mm	Dispenser	Max. 60 notes per bundle Dispensing speed: 7 notes per second 2-4 cassettes, up to 3000 notes per cassette Reject & retract bin
Other Fingerprint reader Contact-less card reader Heat booster Electronic journal Receipt printer: 76mm thermal graphic printer Journal printer: 80mm dot matrix or thermal printer Voltage 100V-240V AC, 50/60Hz Indoor: 0 oC to 40 oC (without heat booster) Outdoor: 35 oC to 40 oC (with heat booster) humidity: 20% to 95% Non-condensing Physical Physical Fingerprint reader Contact-less card reader Heat booster Solve the 40 oC (without heat booster) Height: 1440 mm Width: 450 mm Depth: 870 mm	Security	Dial combination lock mechanism Fraudulent device inhibitor (FDI) EPP shield Privacy filter (optional) Customer awareness mirror Built-in cameras
Printer Journal printer: 80mm dot matrix or thermal printer Voltage 100V-240V AC, 50/60Hz Indoor: 0 oC to 40 oC (without heat booster) Outdoor: 35 oC to 40 oC (with heat booster) humidity: 20% to 95% Non-condensing Physical Physical Journal printer: 80mm dot matrix or thermal printer Head to contact the second of t	Other	Fingerprint reader Contact-less card reader Heat booster
Indoor: 0 oC to 40 oC (without heat booster) Outdoor: 35 oC to 40 oC (with heat booster) humidity: 20% to 95% Non-condensing Height: 1440 mm Width: 450 mm Depth: 870 mm	Printer	Journal printer: 80mm dot matrix or thermal
Environmental Outdoor: 35 oC to 40 oC (with heat booster) humidity: 20% to 95% Non-condensing Height: 1440 mm Width: 450 mm Depth: 870 mm	Voltage	100V-240V AC, 50/60Hz
Physical Width: 450 mm Depth: 870 mm	Environmental	Outdoor: 35 oC to 40 oC (with heat booster)
Weight 269 kg	Physical	Width: 450 mm
	Weight	269 kg

