# Techno ATM
# 7W
## Automated
## Teller Machine

Techno 7W ATM will satisfy customer with stability efficiency, quick withdrawal speed, and new design trend.

- Dispenser: NMD100 (Glory)
- Through the wall type design with new design trend
- Explosion protection safety, (Dial lock & key lock) complying with UL291 L1 Standard
- Easy maintenance

**LG CNS**

**TOSAN** Techno

## Techno ATM
# 7W
## Automated
## Teller Machine

## SPECIFICATIONS

| | | |
|---|---|---|
| **Consumer Interface** | Type | Through The Wall |
| | Maintenance | Rear access |
| | Display | 15 inch LCD with 8 FDKs and Privacy Filter |
| | EPP | Triple DES, PCI 2.0 |
| | Card Reader | Motorized |
| | Audio | High quality public audio, Soundjack |
| **System** | Operating Platform | INTEL Core 2 duo / 4GB RAM, 500GB HDD |
| | Software & Network Interface | Windows 7 / XFS 3.0 |
| | Host Interface | LAN (TCP/IP) |
| **Cash Dispensing Module** | Cassettes | 1-4 cassettes (3,000 notesper 1 cassette) |
| | Dispensing | Max. 100 notesper transaction  /7 notes per second |
| | Retraction | Bundle  retraction, 250 notes |
| | Rejection | Note by note rejection, 150 notes |
| **Card Reader** | Type | Motorized |
| | Magnetic Card | ISO 7811 |
| | Smart Card | EMV Certified |
| | Card Retraction | Up to 20 Cards |
| **Printers** | Receipt Printer | 40 column thermal printer |
| | Journal Printer | Thermal printer |
| **Teller Terminal Unit** | Monitor / key | 7 inch LCD with 8 FDK |
| **Safe** | Certification | UL 291 Level 1 |
| | Locks | Dial Lock + Key Lock |
| **Secure Options** | Antifraud | Anti - skimming Available |
| | UPS | 1 transaction availalble (Optional) |
| | Security Camera | 3 Face, Wrist, Safe (Rear) |
| **Other Facility** | Transaction Guide | LEDFlicker |
| | Power | 220V, 50~60Hz |
| | Heater | Optional |
| | Barcode Reader | 2D |
| **Dimension** | W xD x H /mm | 688 x 1220 x 1520 |
| | Weight | 628kg (4 cassettes) |
| **Environmental** | Temperature | 5~40 C° (Operation) -20~60 C° (Storage) |
| | Humidity | 20%~80% ( Operation) 10%~85% (Storage) |