Techno BCR Cash Recycler

Featured with fast processing speed and big capacity of bulk cash recycling capability, P5800 is the ideal and customized solution for financial institutions and retailers with financial-oriented and teller assisted service needs, such as:

- Teller assisted front desk service or cash sorting in branch back office or cash center.
- Deposit automation in retail back offices, such as supermarkets, stores and gas stations, etc.
- Currency exchange, utility payment and other valueadded service in high cash transaction places like customs and airport.
- Cash in / Cash out Services
- Counterfeit Note Recognition
- 4 Recycling Cassettes with 10.000 Notes Capacity
- Standard UL291 Level 1 safe









FEATURES & BENEFITS

SeNT Serial Number Tracking

• Featured with the OCR (Optical Character Recognition) technology for cash tracing and tracking, P5800 is capable of recording the serial numbers of notes in and out of the machines, providing support of account reconciliation, fraud and cash shrinkage management for the financial institutions.

Optimized Configuration

 Configurable to bulk depository, combination of cash depository only, dispensing only, cash depository and dispensing or cash recycling, easily adjustable to required settings subjecting to local transaction regulations in different networks.

Unrivalled Innovation

• Seamless and intelligent cassette exchange among P5800, deposit machines and recycling ATM, delivers cost-effective yet advanced and secure service for customers. The intelligent and unified cassette in P5800 backs up an end-to-end solution to build up a multiparties' management platform.

Premier Security

 UL291 Level 1 safe, built-in fraud resistant card-reader for staff identification, optional vibration alarm and remote software solution, guarantee 100% transparency cash handling for banks, retailers and CIT companies.

Techno BCR

Cash Recycler

SPECIFICATIONS

Standard 1G (up to 2G) SODIMM Memory	•	
Display 7" LCD touch screen Deposit/Dispensing speed: 8 notes per secon Maximum input/transaction: 200 notes Escrow capacity: 200 notes Escrow capacity: 200 notes Up to 4 recycling cassettes and 1 reject cassette Cassette capacity: 345mm, 2200-2500 notes Reject cassette capacity: max. 2000 notes Supported denominations: 64 4*4 alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight A60kg Barcode Reader Optional	Processor	Intel Atom N270 1.6G CPU (FSB 533MHz)
Deposit/Dispensing speed: 8 notes per secon Maximum input/transaction: 200 notes Escrow capacity: 200 notes Up to 4 recycling cassettes and 1 reject cassette Cassette capacity: 345mm, 2200-2500 notes Reject cassette capacity: max. 2000 notes Supported denominations: 64 4°4 alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional	Memory	Standard 1G (up to 2G) SODIMM Memory
Maximum input/transaction: 200 notes Escrow capacity: 200 notes Up to 4 recycling cassettes and 1 reject cassette Cassette capacity: 345mm, 2200-2500 notes Reject cassette capacity: max. 2000 notes Supported denominations: 64 4*4 alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight A60kg Barcode Reader Optional	Display	7" LCD touch screen
Escrow capacity: 200 notes Up to 4 recycling cassettes and 1 reject cassette Cassette capacity: 345mm, 2200-2500 notes Reject cassette capacity: max. 2000 notes Supported denominations: 64 4*4 alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight A60kg Barcode Reader Optional		Deposit/Dispensing speed: 8 notes per secon-
Cash Recycler Cassette capacity: 345mm, 2200-2500 notes Reject cassette capacity: max. 2000 notes Supported denominations: 64 4*4 alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC card support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Maximum input/transaction: 200 notes
Cash Recycler Cassette capacity: 345mm, 2200-2500 notes Reject cassette capacity: max. 2000 notes Supported denominations: 64 4*4 alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Escrow capacity: 200 notes
Cassette capacity: 345mm, 2200-2500 notes Reject cassette capacity: max. 2000 notes Supported denominations: 64 4*4 alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Qutdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight Barcode Reader Optional	Cash Bacyclar	Up to 4 recycling cassettes and 1 reject
Reject cassette capacity: max. 2000 notes Supported denominations: 64 4*4 alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication Environmental Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional	Casii Recyclei	cassette
Supported denominations: 64 4*4 alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication Communication Environmental Physical Physical Physical Physical Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight A60kg Barcode Reader Optional		Cassette capacity: 345mm, 2200-2500 notes
### A alphanumeric keypad Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer #### 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication #### A alphanumeric keypad Motorized card reader/writer, magnetic/IC car support #### A alphanumeric keypad Support DES, 3DES, RSA encryption PC out an encryption I card: Height 208 to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensing Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight #### 460kg Barcode Reader Optional		Reject cassette capacity: max. 2000 notes
Support DES, 3DES, RSA encryption PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Supported denominations: 64
PCI compliant EPP Motorized card reader/writer, magnetic/IC car support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional	EPP Card reader	4*4 alphanumeric keypad
Motorized card reader/writer, magnetic/IC card support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensin Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Support DES, 3DES, RSA encryption
Support Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Qutdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		PCI compliant EPP
Magnetic card: Hi-Co & Lo-Co track read, ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Qutdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight A60kg Barcode Reader Optional		Motorized card reader/writer, magnetic/IC car
Card reader ISO7811 compliant IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Qutdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		support
IC Card: ISO7816 and EMV4.0 Level 1 compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight A60kg Barcode Reader Optional		Magnetic card: Hi-Co & Lo-Co track read,
Compliant, with card lock function Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight A60kg Barcode Reader Optional		ISO7811 compliant
Receipt Printer 48mm 203DPI graphical thermal printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: °C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		IC Card: ISO7816 and EMV4.0 Level 1
Receipt Printer Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication Environmental Environmental Physical Physica		compliant, with card lock
Electronic lock Mechanical combination lock (opt.) Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Qutdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		function
Physical Security Physical Physical Physical Physical Mechanical combination lock (opt.) Standard UL291 Level 1 safe Emvive Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensin Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional	Receipt Printer	48mm 203DPI graphical thermal printer
Physical Security Standard UL291 Level 1 safe EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional	Physical Security	Electronic lock
Physical Security EMV4.0 Level 1 certified Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Mechanical combination lock (opt.)
Physical Security Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Standard UL291 Level 1 safe
Contactless IC card reader, compliant with QPBOC, Mastercard Paypass and Visa Paywave, USB communication (opt.) Communication Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		EMV4.0 Level 1 certified
Paypass and Visa Paywave, USB communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensin Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Contactless IC card reader, compliant with
communication (opt.) Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Environmental Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		QPBOC, Mastercard
Standard TCP-IP connection Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		
Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Environmental Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		communication (opt.)
Dial-up & Wireless Connection option availab Indoor: 0°C to 40°C Environmental Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional	Communication	Standard TCP-IP connection
Environmental Outdoor: -35°C to 50°C Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Dial-up & Wireless Connection option availab
Relative humidity: 20% to 95% non-condensir Height: 960.3mm Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional	Environmental	Indoor: 0°C to 40°C
Physical Physical Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Outdoor: -35°C to 50°C
Physical Width: 538mm Depth: 1161.8mm Weight 460kg Barcode Reader Optional		Relative humidity: 20% to 95% non-condensir
Depth: 1161.8mm Weight 460kg Barcode Reader Optional	Physical	Height: 960.3mm
Weight 460kg Barcode Reader Optional		Width: 538mm
Barcode Reader Optional		Depth: 1161.8mm
	Weight	460kg
Finger Print Scanner Optional	Barcode Reader	Optional
	Finger Print Scanner	Optional