

S910

Mobile Payment Terminal

The S910 is a cost-effective mobile point of sale terminal, packed with the most complete range of payment industry certifications ever and is manufactured to the highest of global standards using state-of-the-art technology and high-end materials.

Designed to offer GPRS communication, large memory and high capacity Li-ion rechargeable battery, the pocket-sized S910 is the hospitality & restaurant industry's preferred choice, where portability, usability and seamless customer interaction are key requirements. Merchants adore the S910's elegant sleek chassis, and the faster transaction times powered by a high-tech processor.

- High Capacity Battery
- GPRS Communication
- High Speed Printer
- PCI PTS 4.x, SRED





S910

Mobile Payment Terminal

SPECIFICATIONS

FEATURES & BENEFITS

- PCI PTS 4.x, SRED
- 2.4 inch colour touch screen display
- Paper roll diameter: 40mm
- High speed ARM 11 processor
- Large capacity battery
- GPRS communication

Processor	32-bit ARM 11
Memory	80MB standard (16MB Flash 64MB DDR)
Display	2.4 inch 240 x 320 pixels colour TFT LCD
Keypad	10 numeric & letter keys 8 function keys 1 on/off key
Magnetic Card Reader	Track 1 / 2 / 3 bi-directional
Smart Card Reader	EMV Level 1 & Level 2 certified
Card Slots	1 SAM & 1 SIM
Printer	Thermal printer (30 lps) Paper roll width / diameter: 58mm / 40mm
Audio	Speaker, 90dB
Battery	Longer lasting Li-ion battery 2200mAh 3.7V
Communications	GPRS
Peripheral Ports	1 Micro USB (OTG) DUKPT, Master/Session, 3DES
Security	ANSI / ISO9564 Format 0, 1, 3 PIN Ciphered Key Algorithm ANSI X 9.9 / X9.19 MAC Algorithm
Environmental	-10°C to 50°C (14°F to 122°F) operating temperature 0°C to 45°C (32°F to 113°F) battery charging temperature -20°C to 70°C (-4°F to 158°F) storage temperature 10%-93% relative humidity, non-condensing
Voltage	Input: 100~240VAC, 50Hz / 60Hz, 0.2A Output: 5V DC, 1A
Physical	L x W x H: 158 x 78 x 56mm
Weight	306g with battery
Certifications	PCI PTS 4.x, SRED EMV Contact L1 & L2