

Techno Retail POS

# 335

**Payment Terminal  
Solutions**

The Techno 335 offers an outstanding combination of low-power consumption and high-efficient reliability for a smart compact POS system. The spacesaving and easy-to-service characteristics make this small foot print POS terminal a perfect solution for the retail and hospitality industries. The Techno 335 offers a seamless integration for a variety of peripheral modules such as MSR, Fingerprint, Second Display and Customer Display.

- 15" Resistive Touch
- Intel Bay Trail Processor
- Fanless and Silent
- Easy Swap HDD
- 3-Track MSR Available
- Fingerprint Available
- 2nd Display and Customer Display Available



## Techno Retail POS

# 335

## Payment Terminal Solutions

## SPECIFICATIONS



	<b>Type</b>	D36
<b>Motherboard</b>	<b>Processor</b>	Intel Bay Trail CPU Celeron J1900 2.4GHz
	<b>Chipset</b>	CPU Integrated
	<b>System Memory</b>	1x DDR3L SO-DIMM up to 8GB, 1066/1333MHz
	<b>Graphic Engine</b>	Intel HD graphic DX11
<b>LCD Touch Panel</b>	<b>LCD Size</b>	15" TFT LCD
	<b>Brightness</b>	250 nits
	<b>Resolution</b>	1024 x 768
	<b>Touch Screen</b>	Resistive Touch
	<b>Tilt Adjustment</b>	4° ~ 84°
<b>Storage Device</b>	<b>Hard Drive</b>	1x 2.5" SATA HDD
	<b>Flash Memory</b>	SATA SSD (Option)
<b>Expansion</b>	<b>Mini PCI-E Socket</b>	1
	<b>USB</b>	1x USB3.0/2.0, 6x USB2.0
<b>External I/O Ports</b>	<b>Serial Port</b>	3x RJ45 (powered RS232) (COM1/2 default 5V, COM3 default 12V)
	<b>LAN</b>	1x RJ45
	<b>Cash Drawer</b>	1x RJ11
	<b>Parallel Port</b>	1 (Option) (either 1x Parallel + 4x USB2.0 or 6x USB2.0)
	<b>VGA</b>	1x DB15
	<b>DC Jack</b>	1
	<b>Audio</b>	<b>Internal Speaker</b>
<b>Indicator</b>	<b>LED Indicator</b>	1
<b>Power</b>	<b>Power Adapter</b>	65W / 19V
<b>Communication</b>	<b>Wireless LAN</b>	802.11 b/g/n WLAN card & antenna (Option)
<b>Peripheral (Option)</b>	<b>MSR</b>	3-Track MSR (USB)
	<b>Fingerprint</b>	Fingerprint Reader (USB)
	<b>2nd Display</b>	8.4" without touch
	<b>Customer Display</b>	VFD display 2 x 20 characters (COM)
<b>Certificate</b>	<b>EMC &amp; Safety</b>	FCC Class A, CE Mark, LVD
<b>Environment</b>	<b>Operating Temperature</b>	0°C ~ 35°C
	<b>Storage Temperature</b>	-20°C ~ 60°C
	<b>Humidity</b>	20% ~ 85% RH non-condensing
<b>Dimension</b>	<b>WxDxH</b>	365 x 216 x 343 mm
<b>Weight</b>		5.8 kg
<b>OS</b>	<b>OS Supported</b>	Windows 7, POSReady 7, Windows Embedded 8.1 Industry, Windows 10 IoT Enterprise, Linux